

Billetcooler Cone Spray

BilletCooler air mist nozzles

With this type of nozzle it is possible to utilize air mist cooling in **billet** and **bloom** casters for **rounds** very effectively. The compact block design allows mounting either on horizontal spray rings as well as on vertical nozzle headers. A turn down ratio as wide as 1 : 10 is standard at water pressures between 7.3 and 102 psi at 29 psi constant air pressure provides a wide range of cooling intensities.

The cone spray footprint distributes the liquid closer towards the edges; avoiding overcooling of the area beneath the nozzle position. The characteristic is often utilized with round product casters. Various angles are available to compensate for different spray heights, and meet the requirements of the individual machine types. Large free passages compared to hydraulic and competitor air-mist nozzles result in reducing nozzle clogging tendency. Billetcooler cone spray nozzles cover a flow rate range from .11 to 2.1 gpm.

The benefits

- High turn-down ratio (min./ max. flow rate) 10:1 (max. 14:1) for high flexibility and extended product (steel grade) mix, reduces the number of different nozzle types in the machine
- Compressed air consumption reduced by appr. 40% for lowering operation costs
- High Heat Transfer Coefficient (HTC) for high casting speeds



Nozzle type	Max. water flow rate	Operating water pressure	Max. air flow rate	Operating air pressure	Spray angle
Billetcooler cone spray	2.1 gpm	7.3 – 102 psi	5 SCFM	14.5 – 58 psi	45°/60°/90°

Benchmark data only, individual nozzle data to be specified

- Compact design ideal for spray rings and vertical headers
- Plate connection for easy and maintenance friendly mounting
- Large free passages prevent clogging for high operation safety with improved plant availability
- Successfully installed in most long product air-mist cooling systems worldwide
- Reduced maintenance costs

