


➤ Pneumatic atomizing nozzles, full cone, pressure principle, internal mixing

Series 166.1



Features:

- Version with magnetic valve
- Fine full cone atomization
- Liquid pressure principle
- Internal mixing






Series 166.1

Applications:

- Humidification
- Cooling

Technical data:

- Operating pressure: 0–87 psi
- Voltage: 24 V DC
- Power: 8 W
- Switching frequency: Approx. 500/min
- Protective system: IP 67
- Ambient temperature: +50 °C/+122 °F
- Cable length: 39.37 in
- Material of gasket: EPDM



| Air connection G ₁ | Water connection G ₂ | Weight [lb] |
|-------------------------------|---------------------------------|-------------|
| 1/4 NPT | 1/4 NPT | 0.91 |

| Spray angle | Ordering number | Narrowest free cross section Ø [in] | Liquid pressure p [psi] | | | | | | | | Spray dimensions | | | | |
|-------------|-----------------|-------------------------------------|-------------------------|------------------------------|--------------|------------------------------|-------------|------------------------------|-------------|------------------------------|------------------|-----------------------|-----------------------|-----|----|
| | | | 10 | | 20 | | 40 | | 60 | | | | | | |
| | | | p air [psi] | V _w water [gal/h] | p air [SCFM] | V _w water [gal/h] | p air [psi] | V _w water [gal/h] | p air [psi] | V _w water [gal/h] | p air [psi] | Ø D ₁ [in] | Ø D ₂ [in] | | |
| 20° | 166.115.xx.B2 | 0.02 | 6 | 1.56 | 0.3 | 0.2 | 1.5 | 0.5 | 35 | 2.4 | 0.6 | 44 | 2.9 | 0.7 | |
| | | | 12 | 1.00 | 0.6 | 0.4 | 1.1 | 0.6 | 41 | 2.0 | 0.7 | 49 | 2.5 | 0.8 | |
| | | | 17 | 0.45 | 0.9 | 0.5 | 0.6 | 0.8 | 46 | 1.6 | 0.9 | 55 | 2.2 | 0.9 | |
| | | | — | — | 2.6 | 0.3 | 1.0 | 52 | 1.2 | 1.1 | 61 | 1.8 | 1.1 | 46 | |
| | | | — | — | — | — | — | 58 | 0.8 | 1.2 | 67 | 1.5 | 1.3 | 64 | |
| | | | — | — | — | — | — | 64 | 0.5 | 1.5 | 73 | 1.1 | 1.5 | — | |
| | | | — | — | — | — | — | 70 | 0.3 | 1.6 | 78 | 0.8 | 1.6 | — | |
| | 166.125.xx.B2 | 0.02 | — | — | — | — | — | 75 | 0.1 | 1.8 | 84 | 0.6 | 1.8 | — | |
| | | | 12 | 1.24 | 1.5 | 0.9 | 1.8 | 1.1 | 41 | 2.4 | 1.9 | 49 | 2.8 | 2.3 | 20 |
| | | | 17 | 1.16 | 1.9 | 1.1 | 1.7 | 1.3 | 46 | 2.3 | 2.2 | 55 | 2.7 | 2.5 | 32 |
| 40° | 166.115.xx.B2 | 0.02 | 23 | 1.06 | 2.3 | 1.4 | 1.6 | 1.5 | 52 | 2.2 | 2.4 | 61 | 2.6 | 2.7 | 41 |
| | | | 29 | 0.92 | 2.6 | 1.5 | 1.5 | 1.8 | 58 | 2.1 | 2.6 | 67 | 2.5 | 2.9 | 44 |
| | | | 35 | 0.79 | 3.0 | 1.8 | 1.4 | 2.0 | 64 | 2.0 | 2.8 | 73 | 2.5 | 3.2 | 61 |
| | | | 41 | 0.71 | 3.2 | 1.9 | 1.3 | 2.2 | 70 | 1.9 | 3.1 | 78 | 2.4 | 3.4 | — |
| | | | 46 | 0.53 | 3.7 | 2.2 | 1.2 | 2.4 | 75 | 1.8 | 3.3 | 84 | 2.3 | 3.6 | — |
| | | | 52 | 0.42 | 4.1 | 2.4 | 1.0 | 2.6 | 81 | 1.7 | 3.5 | — | — | — | — |
| | 166.125.xx.B2 | 0.02 | 58 | 0.34 | 4.5 | 2.6 | 0.9 | 2.8 | 87 | 1.6 | 3.7 | — | — | — | — |
| | | | 64 | 0.26 | 4.9 | 2.9 | 0.8 | 3.1 | — | — | — | — | — | — | — |
| | | | 70 | 0.16 | 5.2 | 3.1 | 0.7 | 3.3 | — | — | — | — | — | — | — |
| | | | — | — | — | 3.3 | 0.6 | 3.5 | — | — | — | — | — | — | — |
| | | | — | — | — | 3.5 | 0.5 | 3.7 | — | — | — | — | — | — | — |
| | | | — | — | — | — | — | — | — | — | — | — | — | — | — |





| Spray angle | Type | Ordering number Material number 16 | Narrowest free cross section Ø [in] | Liquid pressure p [psi] | | | | | | | | Spray dimensions | | | | | | | |
|---------------|---------------|---|-------------------------------------|-------------------------|-----------------|---------------------------|-------------|-----------------|---------------------------|-------------|-----------------|---------------------------|-------------|---------------|-----------------------|-----------------------|----|---|---|
| | | | | 10 | | 20 | | 40 | | 60 | | | | | | | | | |
| | | | | p air [psi] | V water [gal/h] | V _n air [SCFM] | p air [psi] | V water [gal/h] | V _n air [SCFM] | p air [psi] | V water [gal/h] | V _n air [SCFM] | p air [psi] | p water [psi] | Ø D ₁ [in] | Ø D ₂ [in] | | | |
| 20° | 166.134.xx.B2 | ● | 0.03 | 17 | 3.5 | 1.6 | 29 | 5.1 | 2.3 | 44 | 7.5 | 3.1 | 55 | 8.6 | 1.6 | 26 | 10 | 2 | 4 |
| | | | | 23 | 3.3 | 1.9 | 35 | 4.8 | 2.6 | 49 | 7.3 | 3.4 | 61 | 8.5 | 1.8 | 41 | 22 | 2 | 4 |
| | | | | 29 | 3.1 | 2.3 | 41 | 4.6 | 2.9 | 55 | 7.1 | 3.7 | 67 | 8.3 | 1.9 | 55 | 29 | 2 | 4 |
| | | | | 35 | 3.0 | 2.6 | 46 | 4.4 | 3.2 | 61 | 6.8 | 4.0 | 73 | 8.1 | 2.1 | 75 | 44 | 3 | 4 |
| | | | | 41 | 2.9 | 2.9 | 52 | 4.3 | 3.5 | 67 | 6.6 | 4.3 | 78 | 7.9 | 2.2 | 87 | 58 | 3 | 4 |
| | | | | 46 | 2.9 | 3.2 | 58 | 4.1 | 3.8 | 73 | 6.4 | 4.6 | 84 | 7.7 | 2.4 | — | — | — | — |
| | | | | 52 | 2.8 | 3.5 | 64 | 4.0 | 4.1 | 78 | 6.2 | 4.9 | — | — | — | — | — | — | — |
| | | | | 58 | 2.7 | 3.8 | 70 | 4.0 | 4.5 | 84 | 6.1 | 5.2 | — | — | — | — | — | — | — |
| | | | | 64 | 2.7 | 4.1 | 75 | 3.9 | 4.8 | — | — | — | — | — | — | — | — | — | — |
| | | | | 70 | 2.6 | 4.5 | 81 | 3.7 | 5.1 | — | — | — | — | — | — | — | — | — | — |
| | | | | 75 | 2.5 | 4.8 | 87 | 3.6 | 5.4 | — | — | — | — | — | — | — | — | — | — |
| | | | | 81 | 2.4 | 5.1 | — | — | — | — | — | — | — | — | — | — | — | — | — |
| | | | | 87 | 2.2 | 5.4 | — | — | — | — | — | — | — | — | — | — | — | — | — |
| | | | | 20 | 6.4 | 3.0 | 23 | 14.1 | 2.8 | 46 | 18.7 | 4.7 | 55 | 24.6 | 2.4 | 12 | 10 | 2 | 4 |
| | | | | 26 | 5.4 | 3.7 | 29 | 11.3 | 3.5 | 52 | 16.5 | 5.4 | 61 | 22.0 | 2.7 | 23 | 22 | 3 | 4 |
| | | | | 32 | 5.3 | 4.2 | 35 | 9.3 | 4.2 | 58 | 14.7 | 6.2 | 67 | 19.9 | 3.0 | 44 | 29 | 2 | 4 |
| 166.142.xx.B2 | ● | 0.10 | 0.10 | 38 | 5.1 | 4.8 | 41 | 8.0 | 4.9 | 64 | 13.0 | 6.9 | 73 | 18.2 | 3.3 | 58 | 44 | 3 | 4 |
| | | | | 44 | 4.6 | 5.5 | 46 | 7.6 | 5.6 | 70 | 11.8 | 7.6 | 78 | 16.8 | 3.6 | 87 | 58 | 3 | 4 |
| | | | | 49 | 4.4 | 6.1 | 52 | 7.5 | 6.2 | 75 | 11.1 | 8.3 | 84 | 15.2 | 3.9 | — | — | — | — |
| | | | | 55 | 4.5 | 6.7 | 58 | 7.2 | 6.8 | 81 | 10.7 | 8.9 | — | — | — | — | — | — | — |
| | | | | 61 | 4.3 | 7.3 | 64 | 6.8 | 7.4 | 87 | 10.5 | 9.5 | — | — | — | — | — | — | — |
| | | | | 67 | 4.0 | 7.8 | 70 | 6.4 | 7.9 | — | — | — | — | — | — | — | — | — | — |
| | | | | 73 | 3.7 | 8.4 | 75 | 5.9 | 8.6 | — | — | — | — | — | — | — | — | — | — |
| | | | | 78 | 3.5 | 9.0 | 81 | 5.8 | 9.2 | — | — | — | — | — | — | — | — | — | — |
| | | | | 84 | 3.3 | 9.5 | 87 | 5.7 | 9.8 | — | — | — | — | — | — | — | — | — | — |

Ordering Type + Material no. = Ordering no.
example: 166.134.xx.B2 + 16 = 166.134.16.B2